

Neocopy 30.01-30.02-30.03



Neocopy 30.01



Neocopy 30.02



Neocopy 30.03

Copier for drawings - Manual or automatic paper feed - Multicopy - With 1/2/3 rolls - Synchronized automatic cut - Speed 300 m/h

Technical Specifications

NEOCOPY 30.01-30.02-30.03		NEOCOPY 30.01-30.02-30.03	
Copy procedure	electrophotographic	Cut	Synchronized automatic cut
Transmission	photoconductor	Warm-up time	5 min (7 min with supply of 120V)
Developing process	bicomponent toner magnetic brush	Copy speed	5,0 m/min (196.85 in/min)
Fixer	fusion roller and belt with three temperature settings	Reproduction scale	1:1 ± 0,5%
Paper	plain, opaque paper 80 - 110 g/m ² translucent 90 - 110 g/m ² polyester film 0,075 - 0,1 mm	Programmable number of drawing repetitions	up to 20
Roll size	Ø max 172 mm, core Ø 76 mm	Ideal atmospheric conditions	temperature: +20° ÷ +28° relative humidity: 30 ÷ 70%
Originals	sheet of paper up to 3 mm (0.118 in) thick	Voltage	230 V / 50 Hz - 240 V / 50 Hz 120 V / 60 Hz - 220 V / 60 Hz
Dimensions of originals	max: 915 mm (36.02 in) wide by any lengths min: 210 mm (8.27 in) wide by 297 mm (11.69 in) long	Electrical outlet	single-phase with ground pole
Dimensions of copies	max: 915 mm (36.02 in) wide by any lengths min: 210 mm (8.27 in) wide by 297 mm (11.69 in) manual feed min: 330 mm (12.99 in) wide by 297 mm (11.69 in) roll feed	current consumed	9A
Paper-feed system	manual: with possibility of modifying upper borders to 60 mm (2.36 in) in + or - with 2 mm (0.08 in) steps. automatic: with 1 (30.01), 2 (30.02), 3 (30.03), keyboards selected rolls possibility of modifying upper borders to 60 mm (2.36 in) in + or - with 2 mm (0.08 in) steps and lower border + 60 mm (2.36 in) and -16 mm (0.63 in) with 2 mm (0.08 in) steps.	Maximum consumption	2000W (1500 a 120V)
		Dimensions (WxHxD)	1450x1100x700 mm (30.01) 1450x1135x750 mm (30.02, 30.03)
		Height, work table	850 mm
		Total weight	170 kg (30.01) approx. 200 kg (30.02) approx. 210 kg (30.03) approx.